

**PHILIPS**

CarePoint



# CarePoint Paging Staff Communication

CarePoint paging is an option to dispatch alarms from the central monitoring station to staff members caring for residents around the building.

If your community elects to use pagers for staff to receive system alarms, CarePoint will be configured with the hardware needed to quickly dispatch pages to staff. Your community can customize the number or devices receiving alarms, and create groups allowing messages to be directed to the appropriate team members across your campus.

## Features

Provides coverage on a variety of campus sizes

Covered by back up paging, which allows staff to still receive alarms in the event the computer station is unavailable

Can be configured to alarm with one of 14 different audible notifications or vibrate to provide an unobtrusive alarm notification

Convenient for staff to carry on a belt clip or in a pocket

Alerts can easily be seen on large LCD display which displays 4 lines of text including alarm information and any special notes which may be critical when providing care to residents

Simple to use and maintain with user friendly interface, one button delete and long battery life

Available in multiple colors allowing assignment of pagers to specific regions of the facility or to staff. Provides easy identification.

# Specifications

## Pagers

<b>Color</b>	Black, Red, Blue, or Green
<b>Frequency</b>	Frequency 408-473MHz
<b>Dimensions</b>	80(L) x 53(W) x 20(H) mm
<b>Viewing Area</b>	46 x 17.36 mm
<b>Display</b>	One Page 4-Lines Total 84 Alphanumeric
<b>Screen</b>	Large Blue Back Light
<b>Performance</b>	Extra Long Battery Life
<b>Alerts</b>	4 Beep Alerts, 10 Melody Alerts
<b>Alert Tone</b>	Loudness 85db @ 30 cm (12 inches)
<b>Alarms</b>	5 Daily Alarm Sets
<b>Modes</b>	Vibration and Sleep Modes
<b>Indicators</b>	Unread Message, Message Full Indicators, Message Time Stamp
<b>Detection</b>	Duplicate Message
<b>Auto Features</b>	Sleep/Scroll
<b>Memory</b>	16 Memory Slots, 10 Sets
<b>Locks</b>	8 Message Locks

## Paging Transmitter

<b>Color</b>	Black
<b>Frequency</b>	Frequency 408-473MHz
<b>Dimensions</b>	9" H x 8.5" W x 2.25" D
<b>Frequency Range</b>	UHF2 (440 – 470MHz) UHF1 (400-430MHz)
<b>Power Output</b>	2 Watts, 5 Watts, 25 Watts
<b>Transmitter FCC ID</b>	RXUSD-125EU2 (Maxson)
<b>Transmitter Canada ID</b>	153B-SD125EU2 (Maxson)
<b>Power Supply Input</b>	12vDC 3.75A (of Higher Amp) AC/DC Adaptor
<b>Operating Temperature</b>	22° F to 140° F
<b>Weight</b>	8.5 lbs.

# Ordering Information

<b>Description</b>	<b>Part Number</b>
Black Pager, Alphanumeric, 4 lines	1900497
Red Pager, Alphanumeric, 4 lines	1901000
Blue Pager, Alphanumeric, 4 lines	1901001
Green Pager, Alphanumeric, 4 lines	1901002
Paging Transmitter, 2 Watt, 467.8 MHz	1900500
Paging Transmitter, 2 Watt, 469.6 MHz	1900501
Paging Transmitter – 5 Watt 469.6 MHz	1900498

